

16-14 Gauge .250 Female Push On, Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

Read More

SKU:	492005
Price:	$15.95
Categories:	Push On

Product Description



16-14 Gaug Fully Insula 100

The Nylon insulatio Transparent nylon a connection and is r insulation has a fla Industry standard c Rated 600 volts ma maximum, signs an 105° C (221° F).

Read More

SKU:	8340

Price: $15.48

Categories: Push On

Product Description



16-14 Gauge 1/4 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).
Read More

SKU: 352145

Price: $24.97

Categories: Ring

Product Description



16-14 Gauge 1/4 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

Read More

SKU: 452145

Price: $14.92

Categories: Ring

Product Description



16-14 Gauge 3/8 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

Read More

SKU: 352385

Price: $24.21

Categories: Ring

Product Description



16-14 Gauge 3/8 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

Read More

SKU:	452385DL
Price:	$19.98
Categories:	Ring

Product Description



16-14 Gaug
High Temp

High temperature b
mate, connect, or t
temperature butt c
temperature applic
applications where
ideal for use in high
motors, ovens or ot
can melt. Construct
continuous operatir
intermittent rating

Read More

SKU: 352565

Price: $24.01

Categories: Ring

Product Description



16-14 Gauge 5/16 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

Read More

SKU: 452565

Price: $14.92

Categories: Ring

Product Description



16-14 Gauge 90 Degree .250 Female Flag Push On Fully Insulated Terminal, Bag of 100

Nylon insulation material is molded onto brazed seam barrel and is resistant to deformation. Funnel entry is formed into inside of insulation to allow for easier wire insulation. Brazed seam will not separated under pressure or operating stress. Clear nylon allows for easy inspection of wire connection. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C. Read More

SKU:	894205
Price:	$17.98
Categories:	Flag

Product Description



16-14 Gaug Terminal, B

Vinyl-insulated butt terminals that are u a single wire. The v insulation and the b type of terminal ba are great for marin that utilize wire to t series is the most e available.The PVC i fastened to the but a flared entry for ea standard color-codi volts maximum, bu

signs and fixtures. Temperature rating: 105° C (221° F).

Read More

SKU: 422005

Price: $15.76

Categories: Butt

Product Description



16-14 Gauge Closed End Connector Terminal, Bag of 100

Closed End connectors are ideal for making a simple connection of two or more wires to make a pigtail connection. These closed end connectors feature translucent nylon insulation and a tin-plated copper sleeve that is rated to be used in up to 300V and is RoHS compliant. Translucent nylon insulation. Tin-plated copper sleeve. Meets UL 94V-2 Flammability Classification. Rated for continuous operating temperature of 105°C (221°F).

Read More

SKU: 901215

Price: $9.92

Categories: Closed End

Product Description



16-14 Gauge High Temp Butt Connector, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).
Read More

SKU:	322005
Price:	$36.42
Categories:	Butt

Product Description