

16-14 Gauge High Temp, .250 Female Push-On Terminal, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 392005

Price: \$28.41

Categories: [Push On](#)

Product Description

16-14 Gauge High Temp, .250 Male Push-On Terminal, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 332005

Price: \$34.83

Categories: [Push On](#)

Product Description



16-14 Gauge Piggy Back, .250 Female Push-On Terminal, Bag Of 100

Push-on, piggy back terminals are female type connectors that mate with male push-on terminals, and have an additional male blade to connect a primary and secondary wire, all in one connection. Push-on, piggy back terminals are popular in auto and marine applications, but are also used in various other electrical applications. Most economical insulated terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

SKU: 400675

Price: \$19.11

Categories: [Piggy Back](#)

Product Description



16.2 Oetiker Style Stepless Clamp, 100 A Bag

13.7-16.2 mm or 35/64-41/64

[Read More](#)

SKU: 16.2-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



16.2 Oetiker Style Stepless Clamp, 25 A Bag

13.7-16.2 mm or 35/64-41/64

[Read More](#)

SKU: 16.2-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



17.0 Oetiker Style Stepless Clamp, 100 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

SKU: 17.0-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



17.0 Oetiker Style Stepless Clamp, 25 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

SKU: 17.0-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



18 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-05

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Blue Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-03

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-07

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-04

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-01

Price: \$23.63

Categories: [18 Gauge](#)

Product Description
