

## 16-14 Gauge Butt Connector Terminal, Bag Of 100



Vinyl-insulated butted seam butt connectors are terminals that are used to mate, connect, or terminate a single wire. The vinyl material acts as an economic insulation and the butted seam is the most common type of terminal barrel. Vinyl-insulated butt connectors are great for marine vehicles, and in other applications that utilize wire to transfer electrical current. This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 422005

**Price:** \$15.76

**Categories:** [Butt](#)

### Product Description

---



Categories: [Butt](#)

## Product Description

---



### 16-14 Gauge High Temp Spade Terminal, 10 Stud, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 362105

**Price:** \$19.68

Categories: [Spade](#)

## Product Description

---



### 16-14 Gauge Female Flag Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 392105

**Price:** \$29.42

**Categories:** [Push On](#)

## Product Description

---

### 16-14 Gauge High Temp, .250 Female Push-On Terminal, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 392005

**Price:** \$28.41

**Categories:** [Push On](#)

## Product Description

---



## 16-14 Gauge High Temp, .250 Male Push-On Terminal, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 332005

**Price:** \$34.83

**Categories:** [Push On](#)

### Product Description

---



## 16-14 Gauge Female Push-On Terminal, Bag Of 100

Push-on, piggy back connectors that mate and have an additional primary and secondary terminal. Push-on, piggy back connectors are ideal for marine applications and other electrical applications. This terminal is available in a variety of sizes and is fastened to butted wire for easier wire entry for easier wire

coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

**SKU:** 400675

**Price:** \$19.11

**Categories:** [Piggy Back](#)

## Product Description

---



### 16.2 Oetiker Style Stepless Clamp, 100 A Bag

13.7-16.2 mm or 35/64-41/64

[Read More](#)

**SKU:** 16.2-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

## Product Description

---



### 16.2 Oetiker Style Stepless Clamp, 25 A Bag

13.7-16.2 mm or 35/64-41/64

[Read More](#)

**SKU:** 16.2-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

## Product Description

---



### **17.0 Oetiker Style Stepless Clamp, 100 A Bag**

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

**SKU:** 17.0-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

## Product Description

---



### **17.0 Oetiker Style Stepless Clamp, 25 A Bag**

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

**SKU:** 17.0-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

## Product Description

---