

### 16-14 Gauge High Temp Spade Terminal, 10 Stud, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

#### Read More

SKU:	362105
Price:	\$19.68
<b>Categories</b> :	<u>Spade</u>

### **Product Description**



# 16-14 Gaug Female Flag Bag Of 100

High temperature b mate, connect, or t temperature butt contemperature applic applications where ideal for use in high motors, ovens or ot can melt. Construct continuous operation intermittent rating

**Developer By PDF Catalog Woocommerce** 

Read More	
SKU:	392105
Price:	\$29.42
Categories	Push On

### **Product Description**



# 16-14 Gauge High Temp, .250 Female Push-On Terminal, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

#### Read More

 SKU:
 392005

 Price:
 \$28.41

 Categories:
 Push On

**Product Description** 



# 16-14 Gauge High Temp, .250 Male Push-On Terminal, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

#### Read More

SKU:	332005
Price:	\$34.83
<b>Categories:</b>	Push On

### **Product Description**



# 16-14 Gaug Female Pus Of 100

Push-on, piggy back connectors that ma and have an addition primary and second Push-on, piggy back marine applications electrical applications terminal available. fastened to butted entry for easier wire coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C. Read More SKU: 400675

Price: \$19.11 Categories: Piggy Back

### **Product Description**



## 16.2 Oetiker Style Stepless Clamp, 100 A Bag

13.7-16.2 mm or 35/64-41/64 <u>Read More</u> **SKU:** 16.2-100 **Price:** \$19.20 **Categories:** Oetiker Style Bag Of 100

**Product Description** 



## 16.2 Oetiker Style Stepless Clamp, 25 A Bag

13.7-16.2 mm or 35/64-41/64
Read More
SKU: 16.2-25
Price: \$6.75
Categories: Oetiker Style Bag Of 25

### **Product Description**



## **17.0 Oetiker Style Stepless** Clamp, 100 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing Read More SKU: 17.0-100

Price:\$19.20Categories:Oetiker Style Bag Of 100

**Product Description** 



## 17.0 Oetiker Style Stepless Clamp, 25 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing Read More SKU: 17.0-25

**Price:** \$6.75

Categories: Oetiker Style Bag Of 25

**Product Description** 

#### WooCommerce PDF Catalog



### 18 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hookup wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### Read More

SKU:	29181-05
Price:	\$23.63
<b>Categories:</b>	18 Gauge

### **Product Description**



### 18 Gauge B Foot Roll

Non Stock, Item Mu up wire is ideal for automotive and ma insulation is moistu protection against i 105°C, rated for 60 exceed the specific J1128. CSA file no. 3 Specifications print where exposure to 221°F or where exp

**Developer By PDF Catalog Woocommerce** 

exceeding 140°F. CSA type TEW FT1. Read More SKU: 29181-03 Price: \$23.63 Categories: <u>18 Gauge</u>

#### **Product Description**



### 18 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hookup wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### Read More

SKU:	29181-07
Price:	\$23.63
<b>Categories:</b>	18 Gauge

**Product Description**