

## 16-14 Gauge High Temp Spade Terminal, 10 Stud, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 362105

**Price:** \$19.68

**Categories:** [Spade](#)

### Product Description

---



## 16-14 Gauge Female Flag Terminal, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)**SKU:** 392105**Price:** \$29.42**Categories:** [Push On](#)

## Product Description

---

### 16-14 Gauge High Temp, .250 Female Push-On Terminal, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)**SKU:** 392005**Price:** \$28.41**Categories:** [Push On](#)

## Product Description

---



## 16-14 Gauge High Temp, .250 Male Push-On Terminal, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 332005

**Price:** \$34.83

**Categories:** [Push On](#)

### Product Description

---



## 16-14 Gauge Female Push-On Terminal, Bag Of 100

Push-on, piggy back connectors that mate and have an additional primary and secondary terminal. Push-on, piggy back connectors are ideal for marine applications and other electrical applications. This terminal is available in a variety of sizes and is fastened to butted wire for easier wire entry for easier wire

coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

**SKU:** 400675

**Price:** ~~\$19.11~~ \$16.41

**Categories:** [Piggy Back](#)

## Product Description

---



### 16.2 Oetiker Style Stepless Clamp, 100 A Bag

13.7-16.2 mm or 35/64-41/64

[Read More](#)

**SKU:** 16.2-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

## Product Description

---



### 16.2 Oetiker Style Stepless Clamp, 25 A Bag

13.7-16.2 mm or 35/64-41/64

[Read More](#)

**SKU:** 16.2-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

## Product Description

---



### 17.0 Oetiker Style Stepless Clamp, 100 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

**SKU:** 17.0-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

## Product Description

---



### 17.0 Oetiker Style Stepless Clamp, 25 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

**SKU:** 17.0-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

## Product Description

---



## 18 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29181-05

**Price:** \$23.63

**Categories:** [18 Gauge](#)

### Product Description

---



## 18 Gauge B Foot Roll

Non Stock, Item Mu  
up wire is ideal for  
automotive and ma  
insulation is moistu  
protection against r  
105°C, rated for 60  
exceed the specific  
J1128. CSA file no. 2  
Specifications print  
where exposure to  
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29181-03

**Price:** \$23.63

**Categories:** [18 Gauge](#)

## Product Description

---



## 18 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29181-07

**Price:** \$23.63

**Categories:** [18 Gauge](#)

## Product Description

---