



## White Polyethylene Tubing 1/4 x 100 Ft

Hydronix Mfg, Polyethylene Tubing 230 Psi @ 70°F, Max 120 Psi @ 150°F. MADE FOR PUSH-IN FITTINGS ONLY

[Read More](#)

**SKU:** PT4-100WH

**Price:** \$15.30

**Categories:** [Poly](#)

### Product Description

---



## White Polyethylene Tubing 1/4 x 500 Ft

Hydronix Mfg, Polyethylene Tubing 230 Psi @ 70°F, Max 120 Psi @ 150°F. MADE FOR PUSH-IN FITTINGS ONLY

[Read More](#)

**SKU:** PT04-WH-0500

**Price:** \$50.98

**Categories:** [Poly](#)

### Product Description

---



## White Polyethylene Tubing 3/8 x 100 Ft

Hydronix Mfg, Polyethylene Tubing 230 Psi @ 70°F, Max 120 Psi @ 150°F. MADE FOR PUSH-IN FITTINGS ONLY

[Read More](#)

**SKU:** PT6-100WH

**Price:** \$22.89

**Categories:** [Poly](#)

### Product Description

---



## White Polyethylene Tubing 3/8 x 500 Ft

Hydronix Mfg, Polyethylene Tubing 230 Psi @ 70°F, Max 120 Psi @ 150°F. MADE FOR PUSH-IN FITTINGS ONLY

[Read More](#)

**SKU:** PT06-WH-0500

**Price:** \$89.24

**Categories:** [Poly](#)

### Product Description

---



## White Polyethylene Tubing 3/8 x 500 Ft

John Guest Mfg, Polyethylene Tubing 230 Psi @ 70°F, Max 120 Psi @ 150°F.

[Read More](#)

**SKU:** PE-12-EI-0500F-W

**Price:** \$119.28

**Categories:** [Poly](#)

### Product Description

---



## Wire Auger With O-Ring, Replacement For Cecilware #CD101L

Fits Models GB1M-IT, GB2M5.5-IT, GB3M-10-IT, GB3M-5.5-IT, GB4M-IT, GB5M-IT

[Read More](#)

**SKU:** CD101L

**Price:** \$24.02

**Categories:** [Cecilware](#)

### Product Description

Wire Auger With O-Ring

---

## Wire Nut Kit 158 Pieces

40-Grey, 40-Blue, 50-Orange, 18-Yellow, and 10-Red Connectors

[Read More](#)

**SKU:** ABN158

**Price:** \$16.42

**Categories:** [Wire Nuts](#)



### Product Description

---

## Wire Nuts 18-10 Red, Box Of 100

UL Listed For Pressure Type Wire Connector, For Solid and /Or Stranded Wire Temperature Rating 105°C (221°F), 300V Or 600V Maximum Building Wire

[Read More](#)

**SKU:** EWN66

**Price:** \$9.48

**Categories:** [Wire Nuts](#)



### Product Description

---



## Wire Nuts 20-14 Yellow, Box Of 100

UL Listed For Pressure Type Wire Connector, For Solid and /Or Stranded Wire Temperature Rating 105°C (221°F), 300V Or 1000V Maximum Building Wire. Minimum AWG 3 #20 - maximum AWG 1 #20 W/2 #14 W/1 #16

[Read More](#)

**SKU:** EWN44

**Price:** \$9.21

**Categories:** [Wire Nuts](#)

### Product Description

---



## Wire Nuts 20-16 Orange, Box Of 100

UL Listed For Pressure Type Wire Connector, For Solid and /Or Stranded Wire Temperature Rating 105°C (221°F), 300V Or 1000V Maximum Building Wire. Minimum AWG 1#18 w/1#20 - maximum AWG 4 #16 w/1 #20

[Read More](#)

**SKU:** EWN33

**Price:** \$8.42

**Categories:** [Wire Nuts](#)

### Product Description

---



## Wire Nuts 22-16 Blue, Box Of 100

The industry standard twist-on connector with top quality, performance and durability. Color-coded for easy size selection. Tight, square-wire spring makes quick, secure connections for positive continuity. Tough, thermoplastic shell shields against environmental extremes. Resists chemical action from hydrocarbons, diluted acid or alkaline solutions. Flame-retardant properties resist heat distortion up to 105 °C (221 °F). High-dielectric shell features deep skirt design to prevent exposure of bare wire. Copper-to-copper connections only Connection rated at 600 V Max. for building wiring and rated at 1,000 V Max. in lighting fixtures/luminaries and signs

[Read More](#)

**SKU:** EWN22

**Price:** \$8.42

**Categories:** [Wire Nuts](#)

### Product Description

---



## Wire Nuts 22-16 Grey, Box Of 100

Fan Wire Nut, The industry standard twist-on connector with top quality, performance and durability. Color-coded for easy size selection. Tight, square-wire spring makes quick, secure connections for positive continuity. Tough, thermoplastic shell shields against environmental extremes. Resists chemical action from hydrocarbons, diluted acid or alkaline solutions. Flame-retardant properties resist heat distortion up to 105 °C (221 °F). High-dielectric shell features deep skirt design to prevent exposure of bare wire. Copper-to-copper connections only Connection rated at 600 V Max. for building wiring and rated at 1,000 V Max. in lighting fixtures/luminaries and signs

copper connections only. Connection rated at 600 V Max. for building wiring and rated at 1,000 V Max. in lighting fixtures/luminaries and signs

[Read More](#)

**SKU:** EWN11

**Price:** \$8.26

**Categories:** [Wire Nuts](#)

## Product Description

---