



17.0 Oetiker Style Stepless Clamp, 100 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

SKU: 17.0-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



17.0 Oetiker Style Stepless Clamp, 25 A Bag

14.5-17.0 mm or 37/64-43/64 Fits BB610 And 512-072 Tubing

[Read More](#)

SKU: 17.0-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



18 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-05

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge B Foot Roll

Non Stock, Item Mu
up wire is ideal for
automotive and ma
insulation is moistu
protection against r
105°C, rated for 60
exceed the specific
J1128. CSA file no. 2
Specifications print
where exposure to
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-03

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-07

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-04

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-01

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-02

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18 Gauge Yellow Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 18 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29181-06

Price: \$23.63

Categories: [18 Gauge](#)

Product Description



18.5 Oetiker Style Stepless Clamp, 100 A Bag

15.3-18.5 mm or 39/64-47/64

[Read More](#)

SKU: 18.5-100

Price: \$23.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



18.5 Oetiker Style Stepless Clamp, 25 A Bag

15.3-18.5 mm or 39/64-47/64


[Read More](#)

SKU: 18.5-25

Price: \$8.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



180 Grit Sanding Blocks, 10 Pack

Sanding Sponge, 2.7" L x 3.9" W x 1" H, Washable and Reusable Sanding Blocks, Used For Resurfacing Stainless Steel Equipment.

[Read More](#)

SKU: QMP519

Price: \$23.38

Categories: [Cleaners](#)

Product Description
