



## 20 Gauge Blue Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

**SKU:** 11201-03

**Price:** \$16.93

**Categories:** [20 Gauge](#)

### Product Description

---



## 20 Gauge B 100 Foot R

Non-Stock, Item Mu  
known as AWG wire  
marine, industrial, a  
20 gauge wire is co  
copper and polyvinyl  
wire features a smo  
and ideal for pulling  
can be used on orig  
projects. Single con

polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

**SKU:** 11201-07

**Price:** \$16.93

**Categories:** [20 Gauge](#)

## Product Description

---



## 20 Gauge Green Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

**SKU:** 11201-04

**Price:** \$16.93

**Categories:** [20 Gauge](#)

## Product Description

---



## 20 Gauge Red Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

**SKU:** 11201-01

**Price:** \$16.93

**Categories:** [20 Gauge](#)

### Product Description

---



## 20 Gauge White Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation.

Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

**SKU:** 11201-02

**Price:** \$16.93

**Categories:** [20 Gauge](#)

## Product Description

---



## 20 Gauge Yellow Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

**SKU:** 11201-06

**Price:** \$16.93

**Categories:** [20 Gauge](#)

## Product Description

---



## 21.0 Oetiker Style Stepless Clamp, 100 A Bag

17.8-21.0 mm or 45/64-53/64

[Read More](#)

**SKU:** 21.0-100

**Price:** \$24.20

**Categories:** [Oetiker Style Bag Of 100](#)

### Product Description

---



## 21.0 Oetiker Style Stepless Clamp, 25 A Bag

17.8-21.0 mm or 45/64-53/64

[Read More](#)

**SKU:** 21.0-25

**Price:** \$9.72

**Categories:** [Oetiker Style Bag Of 25](#)

### Product Description

---



## 22-18 Gauge #10 Stud Ring, High Temp Terminal, Bag of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 351105

**Price:** \$22.84

**Categories:** [Ring](#)

### Product Description

---

## 22-18 Gauge #10 Stud Ring, Vinyl Insulated Terminal, Bag of 100



This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

**SKU:** 451105

**Price:** \$16.47

**Categories:** [Ring](#)

## Product Description

---



### 22-18 Gauge #4 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

**SKU:** 451045

**Price:** \$12.61

**Categories:** [Ring](#)

## Product Description

---



### 22-18 Gauge Temp Termi

High temperature b  
mate, connect, or t  
temperature butt co  
temperature applic  
applications where  
ideal for use in high  
motors, ovens or ot  
can melt. Construct  
continuous operatin  
intermittent rating

[Read More](#)

**SKU:** 35100

**Price:** \$24.15

**Categories:** [Ring](#)

## Product Description

---