2.0 Liter or 64 Ounce Stainless Steel Pitcher

8 Cups Or 2.0 Liter With Graduated Lines In Ounces And Milliliters Inside Pitcher

Read More

SKU: 64SSPIT

Price: $37.73

Categories: Beverage

Product Description

2.8 Oz 100% Clear Silicone Sealant USDA Authorized

Protect and seal with 100% silicone rubber Waterproof, weatherproof, won't crack, dry out or crumble.Meets Fed. Spec.TT-S-001543A, Class A USDA authorized for use in federally inspected meat and poultry plants. Meets requirements of FDA Regulation No. 21CFR177.2600. CID-A-A-272. Type IV

Read More

SKU: DC732-3C

Price: $9.71

Categories: Sealants

Product Description

---

20 Gauge Black Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.
Read More

SKU:	11201-05
Price:	$16.93
Categories:	20 Gauge

Product Description

---

20 Gauge B
Foot Roll

Non-Stock, Item Mu
known as AWG wire
marine, industrial, a
20 gauge wire is co
copper and polyvin
wire features a smo
and ideal for pulling
can be used on orig
projects. Single con
polyvinyl chloride in

Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.
Read More

SKU: 11201-03

Price: $17.06

Categories: 20 Gauge

Product Description

---

20 Gauge Brown Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.
Read More

SKU: 11201-07

Price: $16.93

Categories: 20 Gauge

Product Description

---

20 Gauge Green Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.
Read More

SKU:	11201-04
Price:	$16.93
Categories:	20 Gauge

Product Description

---

20 Gauge R
Foot Roll

Non-Stock, Item Mu
known as AWG wire
marine, industrial, a
20 gauge wire is co
copper and polyvin
wire features a smo
and ideal for pulling
can be used on orig
projects. Single con
polyvinyl chloride in

Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.
Read More

SKU: 11201-01

Price: $16.93

Categories: 20 Gauge

Product Description

---

20 Gauge White Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.
Read More

SKU: 11201-02

Price: $16.93

Categories: 20 Gauge

Product Description

---

20 Gauge Yellow Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F).Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

Read More

SKU: 11201-06

Price: $16.93

Categories: 20 Gauge

Product Description

21.0 Oetiker Style Stepless Clamp, 100 A Bag

17.8-21.0 mm or 45/64-53/64

Read More

SKU: 21.0-100

Price: $24.20

Categories: Oetiker Style Bag Of 100

Product Description

21.0 Oetiker Style Stepless Clamp, 25 A Bag

17.8-21.0 mm or 45/64-53/64

Read More

SKU: 21.0-25

Price: $9.72

Categories: Oetiker Style Bag Of 25

Product Description

22-18 Gauge #10 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

Read More

SKU: 351105

Price: $22.84

Categories: Ring

Product Description