



19.8 Oetiker Style Stepless Clamp, 100 A Bag

16.6-19.8 mm or 21/32-25/32

[Read More](#)

SKU: 19.8-100

Price: \$23.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



19.8 Oetiker Style Stepless Clamp, 25 A Bag

16.6-19.8 mm or 21/32-25/32

[Read More](#)

SKU: 19.8-25

Price: \$8.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



2 1/2 Inch Inline Filters Clip, Screw Mount

Fits Filter Series, K5000 And IAP

[Read More](#)

SKU: PPC212W

Price: \$1.05

Categories: [Inline](#)

Product Description



2 Inch Inline Filters Clip, Screw Mount

Fits Filter Series, K2000, SCL, SL, CL, IAC.

[Read More](#)

SKU: PPC204W

Price: \$0.98

Categories: [Inline](#)

Product Description

2 Wide Bib Incline Rack



Comes With Caps And Extensions To Add More Racks, Item Is For Will Call Only Or Can Be Drop Shipped From Mfg, Box Of 4

[Read More](#)

SKU: 2-BIFJ

Price: \$59.44

Categories: [Bib Accessories](#)

Product Description

2-Piece Flexible Black Rubber Lid And Lid Plug, Replacement For Vita-Mix #001191



Fits Models 1002, 5012, 56500-2, Bar Boss 5039, BarBoss, BarBoss MP, Drink Machine 2-Speed, Drink Machine 2-Step Timer, Drink Machine Variable Speed, VM0100, VM0100A, Vita-Prep, Vita-Prep 3, Vita-Pro

[Read More](#)

SKU: 001191

Price: \$24.41

Categories: [Vita-Mix](#)

Product Description

2-Piece Flexible Black Rubber Lid And Lid Plug



2.8 Oz 100% Clear Silicone Sealant USDA Authorized

Protect and seal with 100% silicone rubber Waterproof, weatherproof, won't crack, dry out or crumble. Meets Fed. Spec. TT-S-001543A, Class A USDA authorized for use in federally inspected meat and poultry plants. Meets requirements of FDA Regulation No. 21CFR177.2600. CID-A-A-272. Type IV

[Read More](#)

SKU: DC732-3C

Price: \$9.71

Categories: [Sealants](#)

Product Description



20 Gauge Black 100 Foot Roll

Non-Stock, Item Must be ordered. This wire is known as AWG wire and is used in marine, industrial, and automotive applications. 20 gauge wire is composed of copper and polyvinyl chloride (PVC) insulation. This wire features a smooth finish and is ideal for pulling through conduits. It can be used on original equipment or for repair projects. Single conductor polyvinyl chloride insulated wire operates at temperatures from 40°F to 176°F. Meets requirements of J1128, Ford M1L56A

[Read More](#)

SKU: 11201

Price: \$16.9

Categories: [20 Gauge](#)

Product Description



20 Gauge Blue Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

SKU: 11201-03

Price: \$16.93

Categories: [20 Gauge](#)

Product Description



20 Gauge Brown Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

SKU: 11201-07

Price: \$16.93

Categories: [20 Gauge](#)

Product Description



20 Gauge Green 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation.

Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

SKU: 11201-04

Price: \$16.93

Categories: [20 Gauge](#)

Product Description



20 Gauge Red Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

SKU: 11201-01

Price: \$16.93

Categories: [20 Gauge](#)

Product Description
