



20 Gauge White Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

SKU: 11201-02

Price: \$16.93

Categories: [20 Gauge](#)

Product Description



20 Gauge Yellow Primary Wire 100 Foot Roll

Non-Stock, Item Must Be Ordered. Primary wire, also known as AWG wire, is commonly used in automotive, marine, industrial, and general electrical applications. 20 gauge wire is constructed of single conductor copper and polyvinyl chloride (PVC) insulation. Primary wire features a smooth surface, making it easy to use and ideal for pulling through conduit. 20 gauge wire can be used on original equipment or replacement projects. Single conductor copper stranded with a polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

polyvinyl chloride insulation. Rated for 60 volts. Insulation operates optimally between -40°C to 80°C (-40°F to 176°F). Meets or exceeds SAE specification J1128, Ford M1L56A, & Chrysler MS3450.

[Read More](#)

SKU: 11201-06

Price: \$16.93

Categories: [20 Gauge](#)

Product Description



21.0 Oetiker Style Stepless Clamp, 100 A Bag

17.8-21.0 mm or 45/64-53/64

[Read More](#)

SKU: 21.0-100

Price: \$24.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



21.0 Oetiker Style Stepless Clamp, 25 A Bag

17.8-21.0 mm or 45/64-53/64

[Read More](#)

SKU: 21.0-25

Price: \$9.72

Categories: [Oetiker Style Bag Of 25](#)

Product Description



22-18 Gauge #10 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 351105

Price: \$22.84

Categories: [Ring](#)

Product Description



22-18 Gauge #10 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

SKU: 451105

Price: \$16.47

Categories: [Ring](#)

Product Description



22-18 Gauge #4 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

SKU: 451045

Price: \$12.61

Categories: [Ring](#)

Product Description

22-18 Gauge #6 Stud Ring, High Temp Terminal, Bag of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 351065

Price: \$24.15

Categories: [Ring](#)

Product Description

22-18 Gauge #6 Stud Ring, Vinyl Insulated Terminal, Bag of 100



This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

SKU: 451065

Price: \$12.59

Categories: [Ring](#)

Product Description



22-18 Gauge #8 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 351085

Price: \$21.55

Categories: [Ring](#)

Product Description



22-18 Gauge Insulated Terminal

This series is the most available. The PVC is fastened to the butt with a flared entry for easy maximum, building and fixtures. Industrial wire range. Temperature

[Read More](#)

SKU: 45108

Price: \$17.43

Categories: [Ring](#)

Product Description



22-18 Gauge .110 Female Push On Terminal, Bag Of 100

Vinyl-insulated push-on terminals are female and male blade type connectors that mate with each other to connect or disconnect a wired connection. The vinyl material is an economic insulation that seals the terminal and wire connection. Vinyl-insulated push-on terminals are commonly used in auto and marine vehicles, but can be used in various other electrical applications as well. This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 491185

Price: \$16.42

Categories: [Push On](#)

Product Description
