

## 22-18 Gauge .250 Female Push On Fully Insulated Terminal, Bag of 100



The Nylon insulation sleeve is molded onto the barrel. Transparent nylon allows for easy inspection of connection and is resistant to deformation. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 490105

**Price:** \$17.32

**Categories:** [Push On](#)

### Product Description

---



## 22-18 Gauge Terminal, B

Vinyl-insulated push-on blade type connector. This terminal can connect or disconnect wire. The material is an economical terminal and wire connector. These terminals are common in vehicles, but can be used in many applications as well. The insulated terminal is securely fastened. The insulation has a flared entry. Industry standard color-coding indicates wire range.

Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 431005

**Price:** \$13.74

**Categories:** [Push On](#)

## Product Description

---



## 22-18 Gauge 1/4 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 351145

**Price:** \$23.84

**Categories:** [Ring](#)

## Product Description

---



## 22-18 Gauge 1/4 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

**SKU:** 451145

**Price:** \$15.66

**Categories:** [Ring](#)

### Product Description

---



## 22-18 Gauge 5/16 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 351565

**Price:** \$23.19

**Categories:** [Ring](#)

## Product Description

---



### 22-18 Gauge 5/16 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

**SKU:** 451565

**Price:** \$15.15

**Categories:** [Ring](#)

## Product Description

---



### 22-18 Gauge Terminal, B

Vinyl-insulated butted terminals that are used on a single wire. The vinyl insulation and the barrel type of terminal barrel are great for marine applications that utilize wire to terminate. This series is the most economical available. The PVC insulation is fastened to the butted wire with a flared entry for easier

standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 421005

**Price:** \$15.76

**Categories:** [Butt](#)

## Product Description

---



## 22-18 Gauge Closed End Connector Terminal, Bag of 100

Closed End connectors are ideal for making a simple connection of two or more wires to make a pigtail connection. These closed end connectors feature translucent nylon insulation and a tin-plated copper sleeve that is rated to be used in up to 300V and is RoHS compliant. Translucent nylon insulation. Tin-plated copper sleeve. Meets UL 94V-2 Flammability Classification. Rated for continuous operating temperature of 105°C (221°F).

[Read More](#)

**SKU:** 901205

**Price:** \$11.50

**Categories:** [Closed End](#)

## Product Description

---

## 22-18 Gauge High Temp Butt Connector, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 321005

**Price:** \$27.76

**Categories:** [Butt](#)

### Product Description

---

## 22-18 Gauge High Temp Fork Terminal, 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 36110

**Price:** \$19.68

**Categories:** [Spade](#)

## Product Description

---



## 22-18 Gauge Piggy Back, .250 Female Push-On Terminal, Bag Of 100

Push-on, piggy back terminals are female type connectors that mate with male push-on terminals, and have an additional male blade to connect a primary and secondary wire, all in one connection. Push-on, piggy back terminals are popular in auto and marine applications, but are also used in various other electrical applications. Most economical insulated terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

**SKU:** 400665

**Price:** \$19.89

**Categories:** [Piggy Back](#)

## Product Description

---



## 28.6 Oetiker Style Stepless Clamp, 100 A Bag

[Read More](#)

**SKU:** 28.6-100

**Price:** \$23.20

**Categories:** [Oetiker Style Bag Of 100](#)

### Product Description

---