

22-18 Gauge 5/16 Stud Ring, High Temp Terminal, Bag of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 351565

Price: \$23.19

Categories: [Ring](#)

Product Description

22-18 Gauge Vinyl Insula 100



This series is the most available. The PVC is fastened to the butt with a flared entry for easy maximum, building and fixtures. Industrial wire range. Temperature

[Read More](#)

SKU: 451565

Price: \$15.19

Categories: [Ring](#)

Product Description



22-18 Gauge Butt Connector Terminal, Bag Of 100

Vinyl-insulated butted seam butt connectors are terminals that are used to mate, connect, or terminate a single wire. The vinyl material acts as an economic insulation and the butted seam is the most common type of terminal barrel. Vinyl-insulated butt connectors are great for marine vehicles, and in other applications that utilize wire to transfer electrical current. This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 421005

Price: \$15.76

Categories: [Butt](#)

Product Description



22-18 Gauge Closed End Connector Terminal, Bag of 100

Closed End connectors are ideal for making a simple connection of two or more wires to make a pigtail connection. These closed end connectors feature translucent nylon insulation and a tin-plated copper sleeve that is rated to be used in up to 300V and is RoHS compliant. Translucent nylon insulation. Tin-plated copper sleeve. Meets UL 94V-2 Flammability Classification. Rated for continuous operating temperature of 105°C (221°F).

[Read More](#)

SKU: 901205

Price: \$11.50

Categories: [Closed End](#)

Product Description

22-18 Gauge Connector,



High temperature butt connector, mate, connect, or terminate high temperature butt connector applications where high temperature applications where high temperature applications where ideal for use in high temperature applications where ideal for use in high temperature applications where motors, ovens or other high temperature applications where ideal for use in high temperature applications where can melt. Constructed for high temperature applications where ideal for use in high temperature applications where continuous operating temperature of 105°C (221°F) intermittent rating of 150°C (302°F).

[Read More](#)

SKU: 32100

Price: \$27.7

Categories: [Butt](#)

Product Description



22-18 Gauge High Temp Spade Terminal, 10 Stud, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 361105

Price: \$19.68

Categories: [Spade](#)

Product Description



22-18 Gauge Female Push-On Piggy Back Terminal, Bag Of 100

Push-on, piggy back connectors that mate and have an additional primary and secondary terminal. Push-on, piggy back connectors are ideal for marine applications and electrical applications.

terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

SKU: 400665

Price: \$19.89

Categories: [Piggy Back](#)

Product Description



22.6 Oetiker Style Stepless Clamp, 100 A Bag

19.4-22.6 mm or 49/64-57/64

[Read More](#)

SKU: 22.6-100

Price: \$23.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



22.6 Oetiker Style Stepless Clamp, 25 A Bag

19.4-22.6 mm or 49/64-57/64

[Read More](#)

SKU: 22.6-25

Price: \$8.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



28.6 Oetiker Style Stepless Clamp, 100 A Bag

[Read More](#)

SKU: 28.6-100

Price: \$23.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



28.6 Oetiker Style Stepless Clamp, 25 A Bag

25.4-28.6 mm or 1-1 1/8

[Read More](#)

SKU: 28.6-25

Price: \$8.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



3 Ft Black Extension Cord, 16/3 Sjt看 Rated At 105C, UL Approved For Out Door Use

16/3 Sjt看 105C, Standard NEMA 5-15 receptacle to NEMA 5-15 plug, perfect for every day connections, Rated for outdoor use, UL listed for safety. Commercial Grade.

[Read More](#)

SKU: ELE323-003

Price: \$3.97

Categories: [Cord](#)

Product Description
