

3/4 x 8 Inch Gauge Glass Assembly, Replacement For Wilbur Curtis, WC-2102, 3375002362

Fits Models GEM-3, GEM-5, GEM-8, GEM3, GEM3IF
Read More
SKU: WC-2102

Price: \$15.87 Categories: Wilbur Curtis

Product Description

8"x3/4 Gauge Glass Assembly



3/4 x 8 Inch Gauge Shield, Replacement For Bunn, 01286.0000

Fits Models 1.5 GPR, 1.5 GPR-FF, 2 GPR <u>Read More</u> **SKU:** 01286.0000

 Price:
 \$8.55

 Categories:
 Bunn

Product Description

3/4" Dia x 8" Gauge Shield



3/8 Barb Black Ball Lock Disconnect, Liquid

Mfg CM Becker <u>Read More</u> **SKU:** 3000 **Price:** \$6.86 **Categories:** Bib Accessories

Product Description



Product Description

35 Ft Black Extension Cord, 16/3 Sjtw Rated At 105C, UL Approved For Out Door Use

16/3 Sjtw 105C, Standard NEMA 5-15 receptacle to NEMA 5-15 plug, perfect for every day connections, Rated for outdoor use, UL listed for safety. Commercial Grade.

Read More

SKU:	ELE323-035
Price:	\$20.77
Categories: Cord	



3M Filters Valve In Head With Shroud And Plug, 3/8 Fpt

This high flow valve-in-head assembly has a maximum operating temperature of 100 degrees F (37.8 degrees C), and a pressure range of 25 - 125 psi (172 - 862 kPa). The head can be used on a variety of water filtration systems including ice machines, steamer, combi or proofer ovens, coffee, espresso or hot tea, as well as cold beverage and iced tea filter systems. Fits Cartridges, HF05-MS, HF10-MS, HF15-MS, HF20-MS, HF25-MS, HF30-MS, HF-35-MS, Brew130-MS, PS114, PS124, P124BN, P195BN

Read More

SKU:	62130-03
Price:	\$78.69
Categories:	Cartridges

Product Description



3M Water Filters Cartridge, CFS8112-S, Sold Each Or 12 A Box

3x13 filter, lime scale, sediment taste and odor 1 micron, 1.5 GPM, 10,000 gallon capacity

Read More

SKU: CFS8112-S

Price: \$81.23

Categories: Cartridges



3M Water Filters Cartridge, HF20-MS, Sold Each Or 6 A Box

3M Water Filtration Products HF20-MS Replacement Cartridge effectively combines scale reduction with cyst, sediment and chlorine taste and odor reduction at flow rates up to 1.5 gpm. 3M Water Filtration Products HF20-MS A proprietary slow release scale inhibitor reduces the ability of calcium and magnesium to form on the heating coils and cause downtime and unscheduled service maintenance. Filter Cartridges are o-ring seal type, Certified by NSF to standard 42, FDA CFR-21 Compliant materials, Sanitary Quick Change (SQC) encapsulated cartridge design allows for fast and easy cartridge change-outs with a 1/4 turn, Height:15", Diameter: 4", Flow Rate: 1.5 gpm, Capacity: 9,000 gallons, Micron Rating: 0.5 micron (nominal), Media Type: Carbon Block, Max Water Temp: 100° F, Max Water Pressure: 125 psi, Change Frequency: 6-12 months

Read More

SKU:	HF20-MS
Price:	\$79.98
Categories:	Cartridges



3M Water Filters Cartridge, HF25-MS, Sold Each Or 6 A Box

3M Water Filtration Products HF25-MS Replacement Cartridge effectively combines, sediment and chlorine taste and odor at flow rates up to 1.5 gpm. 3M Water Filtration Products HF25-MS A proprietary slow release scale inhibitor reduces the ability of calcium and magnesium to form on the heating coils and cause downtime and unscheduled service maintenance. For higher turbidity water filtration system, Filter Cartridges are o-ring seal type, Certified by NSF to standard 42, FDA CFR-21 Compliant materials, Sanitary Quick Change (SQC) encapsulated cartridge design allows for fast and easy cartridge change-outs with a 1/4 turn, Height:15", Diameter: 4", Flow Rate: 1.5 gpm, Capacity: 10,000 gallons, Micron Rating: 1.0 micron (nominal), Media Type: Carbon Block, Max Water Temp: 100° F, Max Water Pressure: 125 psi, Change Frequency: 6-12 months

Read More

SKU:	HF25-MS
Price:	\$74.92
Categories:	Cartridges

WooCommerce PDF Catalog



3M Water Filters Cartridge, HF25-S, Sold Each Or 6 A Box

3M Water Filtration Products HF25-S Replacement Cartridge effectively combines, sediment and chlorine reduction for equipment protection and clearer, great tasting ice. 3M Water Filtration Products HF25-S Replacement Cartridge has a built-in scale inhibitor which reduces the ability of calcium and magnesium to precipitate on the evaporator plates as hard scale. For Low Flow Cubers to 750 lbs., High Flow Cubers to 200 lbs. or Flakers to 1,200 lbs. Filter Cartridges require no pre-activation and incorporate carbon block filtration medium and scale inhibitor. Application: Higher Turbidity Water, Ice Filtration System, Filter Cartridges are o-ring seal type, Certified by NSF to standard 42, FDA CFR-21 Compliant materials, Sanitary Quick Change (SQC) encapsulated cartridge design allows for fast and easy cartridge change-outs with a 1/4 turn, Height:15", Diameter: 4", Flow Rate: 1.5 gpm, Capacity: 10,000 gallons, Micron Rating: 1.0 micron (nominal), Media Type: Carbon Block, Max Water Temp: 100° F, Max Water Pressure: 125 psi, Change Frequency: 6-12 months Read More

SKU:HF25-SPrice:\$76.88Categories: Cartridges

WooCommerce PDF Catalog



3M Water Filters Cartridge, HF40-S, Sold Each Or 2 A Box, Uses Head 62130-03

3M[™] High Flow Series Replacement Cartridge, Model HF40-S provides consistent high quality water by reducing particulate*, chlorine taste and odor, cyst**, and bacteria1. Built-in scale inhibition can help to prevent the potentially harmful effects of scale buildup on equipment. Integrated Membrane Pre-Activated Carbon Technology ("I.M.P.A.C.T.") filtration media combines a membrane with a premium activated carbon block to help provide excellent throughput and cartridge life.

Read More

SKU:	HF40-S
Price:	\$126.88
Categories	Cartridges

Product Description



Product Description

4 Gallon Tank 3.2 Gallon Draw Down With 1/4 Mpt

Read More

SKU:	RO TANK
Price:	\$36.32
Categories:	Tanks



4 Gauge Butt Connector Terminal, Bag Of 25

Vinyl-insulated butted seam butt connectors are terminals that are used to mate, connect, or terminate a single wire. The vinyl material acts as an economic insulation and the butted seam is the0 most common type of terminal barrel. Vinyl-insulated butt connectors are great for marine vehicles, and in other applications that utilize wire to transfer electrical current. This series is the most economical insulated terminal available.The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

Read More

SKU:	426005
Price:	\$41.12
Categories:	Butt