



6 Gauge Butt Connector Terminal, Bag Of 25

Vinyl-insulated butted seam butt connectors are terminals that are used to mate, connect, or terminate a single wire. The vinyl material acts as an economic insulation and the butted seam is the most common type of terminal barrel. Vinyl-insulated butt connectors are great for marine vehicles, and in other applications that utilize wire to transfer electrical current. This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 425005

Price: \$32.49

Categories: [Butt](#)

Product Description



6 In 1 Reversible Screwdriver, Made In USA

#1 And #2 Phillips, 3/16 And 9/32 Slotted, 1/4 & 5/16
Hex Nut Driver

[Read More](#)

SKU: SCD61

Price: \$7.87

Categories: [Hand](#)

Product Description



6000 Grain Rechargeable Water Softener, Fpt 3/4 7 Inches Wide x 15 Inches Tall

To Reduce Down, Use Bushings 110A-EB For 1/4 Fpt Or
110A-EC For 3/8 Fpt.

[Read More](#)

SKU: WS6000

Price: \$112.20

Categories: [Softeners](#)

Product Description



7.0 Oetiker Style Stepless Clamp, 25 A Bag

5.8-7.0 mm or 15/64-9/32, Used For 1/4 Poly Tubing

[Read More](#)

SKU: 7.0-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



8 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 8 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29081-05

Price: \$124.97

Categories: [8 Gauge](#)

Product Description

8 Gauge Butt Connector Terminal, Bag Of 25



Vinyl-insulated butted seam butt connectors are terminals that are used to mate, connect, or terminate a single wire. The vinyl material acts as an economic insulation and the butted seam is the most common type of terminal barrel. Vinyl-insulated butt connectors are great for marine vehicles, and in other applications that utilize wire to transfer electrical current. This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 424005

Price: \$20.57

Categories: [Butt](#)

Product Description



8 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 8 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29081-01

Price: \$124.97

Categories: [8 Gauge](#)

Product Description



8 Gauge Wh Foot Roll

Non Stock, Item Must Be Ordered. 8 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29081-02

Price: \$124.94

Categories: [8 Gauge](#)

Product Description



8 Inch Frothing Thermometer With Clip

This frothing thermometer has a range of 30°F to 220°F degrees. It will accurately measure the temperature when heating milk or Turkish coffee to frothing. Features include dial diameter - 1.75", length - 8" stem, NSF approved.

[Read More](#)

SKU: T220-38A

Price: ~~\$8.27~~ \$5.32

Categories: [Thermometers](#)

Product Description



8.0 Oetiker Style Stepless Clamp, 25 A Bag

6.8-8.0 mm or 17/64-5/16

[Read More](#)

SKU: 8.0-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



8.7 Oetiker Style Stepless Clamp, 25 A Bag

7.0-8.7 mm or 9/32-11/32

[Read More](#)

SKU: 8.7-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



8000 Grain Rechargeable Water Softener, Fpt 3/4 7 Inches Wide x 21 Inches Tall

To Reduce Down, Use Bushings 110A-EB For 1/4 Fpt Or 110A-EC For 3/8 Fpt.

[Read More](#)

SKU: WS8000

Price: \$120.33

Categories: [Softeners](#)

Product Description
