

Amprobe Test Leads With Alligator Clips, Rated 1000 Volts

Test lead set connects a compatible electrical test meter to a device for testing. Set includes two lead wires, two threaded test probe tips, and two alligator clips. Polyvinyl chloride (PVC) insulation helps protect hands from shock and heat 2.67" threaded alligator clips have 0.30" jaw opening and teeth that grip the conductor to provide a more secure, hands-free connection than probe tips Meets International Electrotechnical Commission (IEC) safety standard 61010 and is certified for category III installations up to 1,000V

Read More

SKU: TL-100
Price: \$36.64
Categories: Hand

Product Description



Angle Chair Replacement Z8410

Fits Models 20, 20C 20SCR, 30, 30BB, 3 30CBBE, 30CBD, 30 30CHDE, 30CR, 30C 30SBBC, 30SC, 30S 30SCBDE, 30SCDV, 30SCHDE, 30SCHDI 45SCHDEP, 50, 50B 50CBBE, 50CBBES, 50CF, 50CHD, 50CHDE, 50CR, 50CRBB, 50CSA, 50DV, 50F, 50HD, 50S, 50SBB, 50SBBC, 50SC, 50SC-ST, 50SC-STS, 50SCBB, 50SCBBC, 50SCBBE, 50SCBD, 50SCBDE, 50SCBDE-CSA, 50SCBDESW, 50SCDV, 50SCE, 50SCE-ST, 50SCEQT, 50SCEX, 50SCF, 50SCHD, 50SCHDE, 50SCHDEM, 50SCHDEP, 50SCHDM, 50SCRBB, 50SF, 75SCHDEM, 75SCHDM

Read More

SKU: A5-Z8410

Price: \$12.51

Categories: Star

Product Description

Angle Chain Retainer 20/30/50



Angle Stop Max Adapter Valve, Male Compression x Female Compression x Tube 3/8 x 3/8 x 1/4

John Guest Mfg, Sold Each, Less Expensive Then Using Max Adapter And Valve Together

Read More

SKU: LQFA0406F

Price: \$12.13

Categories: Valve



Angle Stop Max Adapter Valve, Male Compression x Female Compression x Tube 3/8 x 3/8

John Guest Mfg, Sold Each, Less Expensive Then Using Max Adapter And Valve Together

Read More

SKU: PPASV-6

Price: \$12.92

Categories: Valve

Product Description



Angle Stop Max Adapter, Lead Free 1/2 Npt x 1/2 Comp x 1/4 Comp

Male Pipe x Female Pipe Swivel x Male Compression Lead Free, Easily Converts Old Style Angle Or Straight Stops To Dual Outlet Valves

Read More

SKU: MAX84NPT

Price: \$11.58

Categories: Adapters



Product Description

Angle Stop Max Adapter, Lead Free 1/2 x 1/2 x 1/4

Male Compression x Female Compression Swivel x Male Compression Lead Free, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

Read More

SKU: MAX84

Price: \$10.23

Categories: Adapters



Product Description

Angle Stop Max Adapter, Lead Free 1/2 x 1/2 x 3/8

Male Compression x Female Compression Swivel x Male Compression Lead Free, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

Read More

SKU: MAX86
Price: \$10.27
Categories: Adapters



Angle Stop Max Adapter, Lead Free 3/8 x 3/8 x 1/4

Male Compression x Female Compression Swivel x Male Compression, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

Read More

SKU: MAX4 **Price:** \$5.41

Categories: Adapters

Product Description



Angle Stop Max Adapter, Lead Free 3/8 x 3/8 x 3/8

Male Compression x Female Compression Swivel x Male Compression, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

Read More

SKU: MAX6 **Price:** \$5.92

Categories: Adapters



Angle Stop, Lead Free, 5/8 Inch. Od Compression x 3/8 Inch Od Compression, Chrome Plated Finish, Multi Turn.

This angle stop features a solid brass construction, a chrome-plated finish, and a celcon stem. All of its features comply with state lead-free requirements.

Read More

SKU: 101584

Price: \$4.43

Categories: Plumbing

Product Description



Aquatec 28 Ounce Accumulator Tank With 3/8 Female Pipe Threads

Convenient 3/8" Female NPT ports. Compact design fits in small spaces, Dimension 8.92" L X 4.84" W X 4.13" H Dampens pump switch cycling/pulsations. Limits harmful spikes/water hammer. Minimizes hydraulic noise NSF food grade materials Easy to install and maintain Mounts in any position with included bracket. Maximum Working Pressure – 125 PSI. Pre-Charge – 20 PSI

Read More

SKU: 30573-0002B

Price: \$51.30
Categories: Pumps



Aquatec Delivery Demand Water Pump 6.0 Gpm 60 Psi With 6 Foot Cord, 115V, 1/2 Fpt

The Aquatec 550 Series Pumps are used to either draw water from a holding tank and pressurize it or boost pressure from a low pressure source. Although designed to operate intermittently many 550 versions can run continuously for several hours at a time. These pumps can be operated either in demand mode (pressure switch controlled) or in delivery mode (controlled by external power switching device). If needed an integral bypass can be used to limit pressure. 5-chamber construction Closed impervious diaphragm Independent symmetrical valves Highest structural integrity Ten point clamping Engineered composite plastics Corrosion resistant metal Pressure switch and transducer options Aquatec 5513 Demand Pump Benefits: Self-priming Unparalleled performance efficiency Whisper quiet at lower flows Minimal pulsations 7 year design life Runs dry without damage Chemically resistant versions Aquatec 5513 Demand Pump Technical Information Aquatec 550 Series Demand Pump Data 5513 550 Series Superflow Pumps Aguatec 550 Series Superflow Pumps Duplex 2 Series Pumps are suited for chemical or beverage and water applications such as city water pressure boost. Built in check valve.

Read More

SKU: 5513

Price: \$163.76

Categories: Pumps

