



Angle Chain Retainer 20/30/50, Replacement For Star #A5- Z8410

Fits Models 20, 20C, 20CE, 20CR, 20S, 20SC, 20SCE, 20SCR, 30, 30BB, 30BD, 30C, 30CBB, 30CBBC, 30CBBE, 30CBD, 30CBDE, 30CDV, 30CE, 30CF, 30CHD, 30CHDE, 30CR, 30CRBB, 30D, 30F, 30HD, 30S, 30SBB, 30SBBC, 30SC, 30SCBB, 30SCBBC, 30SCBBE, 30SCBD, 30SCBDE, 30SCDV, 30SCE, 30SCEX, 30SCF, 30SCHD, 30SCHDE, 30SCHDM, 30SCR, 30SCRBB, 30SF, 45SCHDEP, 50, 50BB, 50BD, 50C, 50CBB, 50CBBC, 50CBBE, 50CBBES, 50CBD, 50CBDE, 50CDV, 50CE, 50CF, 50CHD, 50CHDE, 50CR, 50CRBB, 50CSA, 50DV, 50F, 50HD, 50S, 50SBB, 50SBBC, 50SC, 50SC-ST, 50SC-STs, 50SCBB, 50SCBBC, 50SCBBE, 50SCBD, 50SCBDE, 50SCBDE-CSA, 50SCBDESW, 50SCDV, 50SCE, 50SCE-ST, 50SCEQT, 50SCEX, 50SCF, 50SCHD, 50SCHDE, 50SCHDEM, 50SCHDEP, 50SCHDM, 50SCR, 50SCRBB, 50SF, 75SCHDEM, 75SCHDM

[Read More](#)

SKU: A5-Z8410

Price: \$12.51

Categories: [Star](#)

Product Description

Angle Chain Retainer 20/30/50



Angle Stop Max Adapter Valve, Male Compression x Female Compression x Tube 3/8 x 3/8 x 1/4

John Guest Mfg, Sold Each, Less Expensive Then Using
Max Adapter And Valve Together

[Read More](#)

SKU: LQFA0406F

Price: \$12.13

Categories: [Valve](#)

Product Description



Angle Stop Max Adapter Valve, Male Compression x Female Compression x Tube 3/8 x 3/8 x 3/8

John Guest Mfg, Sold Each, Less Expensive Then Using
Max Adapter And Valve Together

[Read More](#)

SKU: PPASV-6

Price: \$12.92

Categories: [Valve](#)

Product Description



Angle Stop Max Adapter, Lead Free 1/2 x 1/2 x 1/4

Male Pipe x Female Pipe Swivel x Male Compression Lead Free, Easily Converts Old Style Angle Or Straight Stops To Dual Outlet Valves

[Read More](#)

SKU: MAX84NPT

Price: \$11.58

Categories: [Adapters](#)

Product Description



Angle Stop Max Adapter, Lead Free 1/2 x 1/2 x 1/4

Male Compression x Female Compression Swivel x Male Compression Lead Free, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

[Read More](#)

SKU: MAX84

Price: \$10.23

Categories: [Adapters](#)

Product Description



Angle Stop Max Adapter, Lead Free 1/2 x 1/2 x 3/8

Male Compression x Female Compression Swivel x Male Compression Lead Free, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

[Read More](#)

SKU: MAX86

Price: \$10.27

Categories: [Adapters](#)

Product Description



Angle Stop Max Adapter, Lead Free 3/8 x 3/8 x 1/4

Male Compression x Female Compression Swivel x Male Compression, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

[Read More](#)

SKU: MAX4

Price: \$5.41

Categories: [Adapters](#)

Product Description



Angle Stop Max Adapter, Lead Free 3/8 x 3/8 x 3/8

Male Compression x Female Compression Swivel x Male Compression, Easily Converts Angle Or Straight Stops To Dual Outlet Valves

[Read More](#)

SKU: MAX6

Price: \$5.92

Categories: [Adapters](#)

Product Description



Angle Stop, Lead Free, 5/8 Inch. Od Compression x 3/8 Inch Od Compression, Chrome Plated Finish, Multi Turn.

This angle stop features a solid brass construction, a chrome-plated finish, and a celcon stem. All of its features comply with state lead-free requirements.

[Read More](#)

SKU: 101584

Price: \$4.43

Categories: [Plumbing](#)

Product Description



Angle Valve Tube x Fpt 3/8 x 1/4

John Guest Mfg, Sold Each Or 10 A Bag

[Read More](#)

SKU: LQBV450604W

Price: \$6.12

Categories: [Valve](#)

Product Description

Aquatec 28 Ounce Accumulator Tank With 3/8 Female Pipe Threads

Convenient 3/8" Female NPT ports. Compact design fits in small spaces, Dimension 8.92" L X 4.84" W X 4.13" H Dampens pump switch cycling/pulsations. Limits harmful spikes/water hammer. Minimizes hydraulic noise NSF food grade materials Easy to install and maintain Mounts in any position with included bracket. Maximum Working Pressure - 125 PSI. Pre-Charge - 20 PSI

[Read More](#)

SKU: 30573-0002B

Price: \$51.30

Categories: [Pumps](#)

Product Description



Aquatec Delivery Demand Water Pump 6.0 Gpm 60 Psi With 6 Foot Cord, 115V, 1/2 Fpt

The Aquatec 550 Series Pumps are used to either draw water from a holding tank and pressurize it or boost pressure from a low pressure source. Although designed to operate intermittently many 550 versions can run continuously for several hours at a time. These pumps can be operated either in demand mode (pressure switch controlled) or in delivery mode (controlled by external power switching device). If needed an integral bypass can be used to limit pressure. 5-chamber construction Closed impervious diaphragm Independent symmetrical valves Highest structural integrity Ten point clamping Engineered composite plastics Corrosion resistant metal Pressure switch and transducer options Aquatec 5513 Demand Pump Benefits: Self-priming Unparalleled performance efficiency Whisper quiet at lower flows Minimal pulsations 7 year design life Runs dry without damage Chemically resistant versions Aquatec 5513 Demand Pump Technical Information Aquatec 550 Series Demand Pump Data 5513 550 Series Superflow Pumps Aquatec 550 Series Superflow Pumps Duplex 2 Series Pumps are suited for chemical or beverage and water applications such as city water pressure boost. Built in check valve.

[Read More](#)

SKU: 5513

Price: \$152.48

Categories: [Pumps](#)

Product Description
