



10/3 SJ00W Black Round Cord 250 Foot Spool

Non Stock, Item Must Be Ordered. 10/3 300-Volt Portable Cord is ideal for wiring portable tools, small motors and equipment. This cord features 3 copper conductors with wax- and tissue-paper insulation and a rubber jacket. This product is highly flexible with good tensile strength, elongation and aging. Class-K copper conductors, 250 ft. cable offers heat-, moisture- and oil-resistant, flexible rubber jacket, 10-gauge black stranded construction Wax- and tissue paper filler wrapped around the conductors to promote easier removal of the jacket, RoHS compliant, UL listed and CSA certified for indoor and outdoor use

[Read More](#)

SKU: 10-3

Price: \$602.23

Categories: [Cord](#)

Product Description



10/4 SJ00W 250 Foot Spool

Non Stock, Item Must Be Ordered. 10/4 300-Volt Portable Cord is ideal for wiring portable tools, small motors and equipment. This cord features 4 copper conductors with wax- and tissue-paper insulation and a rubber jacket. This product is highly flexible with good tensile strength, elongation and aging. Class-K copper conductors, 250 ft. cable offers heat-, moisture- and oil-resistant, flexible rubber jacket, 10-gauge black stranded construction Wax- and tissue paper filler wrapped around the conductors to promote easier removal of the jacket, RoHS compliant, UL listed and CSA certified for indoor and outdoor use

removal of the jacket, RoHS compliant, UL listed and CSA certified for indoor and outdoor use

[Read More](#)

SKU: 10-4

Price: \$792.50

Categories: [Cord](#)

Product Description



10/4 Sjtow Cord With L14-30P Plug, 8 Foot

Comes With L14-30P Twist Lock Plug On End And #8 Ring Terminal On Ground Wire, 6" Loose Wires Stripped 1/2"

[Read More](#)

SKU: ELE277

Price: \$42.75

Categories: [Cord](#)

Product Description



10/4 Sjtow Cord With L14-30P Plug, 8 Foot, Replacement For Bunn #26858.0000

Fits Models DUAL SH 1.50, DUAL SH 1.75, IC3. Comes With L14-30P Twist Lock Plug On End And #8 Ring Terminal On Ground Wire, 6" Loose Wires Stripped 1/2"


[Read More](#)

SKU: 26858.0000

Price: \$42.75

Categories: [Bunn](#)

Product Description



100-Pack Razor Utility Blades

Fit Box Cutters and Razor Blade Scrapers

[Read More](#)

SKU: 0024-051

Price: \$14.91

Categories: [Hand](#)

Product Description



100-Pack Razor Utility Blades
SK5

With Dispenser

[Read More](#)

SKU: 0024-199

Price: \$17.63

Categories: [Hand](#)

Product Description



10B Split Heel Set, Black, Series III-M4

[Read More](#)

SKU: PH10-138

Price: \$3.10

Categories: [Parts](#)

Product Description



11.3 Oetiker Style Stepless Clamp, 100 A Bag

9.6-11.3 mm or 3/8-7/16

[Read More](#)

SKU: 11.3-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



11.3 Oetiker Style Stepless Clamp, 25 A Bag

9.6-11.3 mm or 3/8-7/16

[Read More](#)

SKU: 11.3-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



11.8 Oetiker Style Stepless Clamp, 100 A Bag

10.1-11.8 mm or 25/64-15/32

[Read More](#)

SKU: 11.8-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



11.8 Oetiker Style Stepless Clamp, 25 A Bag

10.1-11-8 mm or 25/64-15/32

[Read More](#)

SKU: 11.8-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



12 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-05

Price: \$60.99

Categories: [12 Gauge](#)

Product Description
