



11.3 Oetiker Style Stepless Clamp, 100 A Bag

9.6-11.3 mm or 3/8-7/16

[Read More](#)

SKU: 11.3-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



11.3 Oetiker Style Stepless Clamp, 25 A Bag

9.6-11.3 mm or 3/8-7/16

[Read More](#)

SKU: 11.3-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



11.8 Oetiker Style Stepless Clamp, 100 A Bag

10.1-11-8 mm or 25/64-15/32

[Read More](#)

SKU: 11.8-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



11.8 Oetiker Style Stepless Clamp, 25 A Bag

10.1-11-8 mm or 25/64-15/32

[Read More](#)

SKU: 11.8-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



12 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-05

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Blue Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-03

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-07

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-04

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-01

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-02

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Inch #2 Phillips Long Shaft Screwdriver

Magnetic Tip With Plastic Grip. Chrome Vanadium Steel. Overall Size 16"

[Read More](#)

SKU: 4123

Price: \$19.62

Categories: [Hand](#)

Product Description



12-10 Gauge #10 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 353105

Price: \$23.74

Categories: [Ring](#)

Product Description
