



## 11.3 Oetiker Style Stepless Clamp, 100 A Bag

9.6-11.3 mm or 3/8-7/16

[Read More](#)

**SKU:** 11.3-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

### Product Description

---



## 11.3 Oetiker Style Stepless Clamp, 25 A Bag

9.6-11.3 mm or 3/8-7/16

[Read More](#)

**SKU:** 11.3-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

### Product Description

---



## 11.8 Oetiker Style Stepless Clamp, 100 A Bag

10.1-11-8 mm or 25/64-15/32

[Read More](#)

**SKU:** 11.8-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

### Product Description

---



## 11.8 Oetiker Style Stepless Clamp, 25 A Bag

10.1-11-8 mm or 25/64-15/32

[Read More](#)

**SKU:** 11.8-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

### Product Description

---



## 12 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29121-05

**Price:** \$60.99

**Categories:** [12 Gauge](#)

### Product Description

---



## 12 Gauge B Foot Roll

Non Stock, Item Mu  
up wire is ideal for  
automotive and ma  
insulation is moistu  
protection against r  
105°C, rated for 60  
exceed the specific  
J1128. CSA file no. 2  
Specifications print  
where exposure to  
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29121-03

**Price:** \$60.99

**Categories:** [12 Gauge](#)

## Product Description

---



## 12 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29121-07

**Price:** \$60.99

**Categories:** [12 Gauge](#)

## Product Description

---



## 12 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29121-04

**Price:** \$60.99

**Categories:** [12 Gauge](#)

### Product Description

---



## 12 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29121-01

**Price:** \$60.99

**Categories:** [12 Gauge](#)

## Product Description

---



## 12 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29121-02

**Price:** \$60.99

**Categories:** [12 Gauge](#)

## Product Description

---



## 12 Inch #2 Phillips Long Shaft Screwdriver

Magnetic Tip With Plastic Grip. Chrome Vanadium Steel. Overall Size 16"

[Read More](#)

**SKU:** 4123

**Price:** \$19.62

**Categories:** [Hand](#)

### Product Description

---



## 12-10 Gauge #10 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 353105

**Price:** \$23.74

**Categories:** [Ring](#)

### Product Description

---