



12 Gauge Blue Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-03

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-07

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-04

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-01

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 12 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29121-02

Price: \$60.99

Categories: [12 Gauge](#)

Product Description



12 Inch #2 Phillips Long Shaft
Screwdriver

Magnetic Tip With Plastic Grip. Chrome Vanadium Steel. Overall Size 16"

[Read More](#)

SKU: 4123

Price: \$16.62

Categories: [Hand](#)

Product Description



12-10 Gauge
High Temp

High temperature butt
mate, connect, or ter
temperature butt co
temperature applic
applications where
ideal for use in high
motors, ovens or ot
can melt. Construct
continuous operatin
intermittent rating

[Read More](#)**SKU:** 353105**Price:** \$23.74**Categories:** [Ring](#)

Product Description

12-10 Gauge #10 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)**SKU:** 453105**Price:** \$21.53**Categories:** [Ring](#)

Product Description





12-10 Gauge #6 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 353065

Price: \$24.40

Categories: [Ring](#)

Product Description

12-10 Gauge #6 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

SKU: 453065

Price: \$21.32

Categories: [Ring](#)



Product Description



12-10 Gauge #8 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 383085
Price: \$22.39
Categories: [Ring](#)

Product Description



12-10 Gauge Insulated Terminal

This series is the most available. The PVC is fastened to the butt of a flared entry for easy maximum, building and fixtures. Industrial wire range. Temperature

[Read More](#)

SKU: 45308

Price: \$18.73

Categories: [Ring](#)

Product Description
