

12-10 Gauge .250 Female Push On, Fully Insulated Terminal, Bag of 100



This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 490305

Price: \$19.80

Categories: [Push On](#)

Product Description

12-10 Gauge .250 Male Push On, Insulated Terminal, Bag of 100



This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 433005

Price: \$18.49

Categories: [Push On](#)

Product Description



12-10 Gauge 1/2 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

SKU: 453125

Price: \$37.78

Categories: [Ring](#)

Product Description



12-10 Gauge Temp Termi

High temperature b
mate, connect, or t
temperature butt c
temperature applic
applications where
ideal for use in high
motors, ovens or ot
can melt. Construct
continuous operatin
intermittent rating

[Read More](#)

SKU: 353145**Price:** \$25.52**Categories:** [Ring](#)

Product Description

12-10 Gauge 1/4 Stud Ring, Vinyl Insulated Terminal, Bag of 100



This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)**SKU:** 453145**Price:** \$23.25**Categories:** [Ring](#)

Product Description

12-10 Gauge 3/8 Stud Ring, High Temp Terminal, Bag of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 353385

Price: \$27.57

Categories: [Ring](#)

Product Description

12-10 Gauge 3/8 Stud Ring, Vinyl Insulated Terminal, Bag of 100



This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

SKU: 453385DL

Price: \$25.38

Categories: [Ring](#)

Product Description



12-10 Gauge 5/16 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 353565

Price: \$24.99

Categories: [Ring](#)

Product Description



12-10 Gauge Vinyl Insula 100

This series is the most available. The PVC is fastened to the butt with a flared entry for easy maximum, building and fixtures. Industrial wire range. Temper

[Read More](#)

SKU: 453565**Price:** \$22.14**Categories:** [Ring](#)

Product Description



12-10 Gauge 90 Degree .250 Female Flag Push On Fully Insulated Terminal, Bag of 50

Nylon insulation material is molded onto brazed seam barrel and is resistant to deformation. Funnel entry is formed into inside of insulation to allow for easier wire insulation. Brazed seam will not separate under pressure or operating stress. Clear nylon allows for easy inspection of wire connection. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)**SKU:** 894305**Price:** \$17.98**Categories:** [Flag](#)

Product Description



12-10 Gauge Butt Connector Terminal, Bag Of 100

Vinyl-insulated butted seam butt connectors are terminals that are used to mate, connect, or terminate a single wire. The vinyl material acts as an economic insulation and the butted seam is the most common type of terminal barrel. Vinyl-insulated butt connectors are great for marine vehicles, and in other applications that utilize wire to transfer electrical current. This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

SKU: 423005

Price: \$19.97

Categories: [Butt](#)

Product Description



12-10 Gauge Closed End Connector Terminal, Bag of 100

Closed End connectors are ideal for making a simple connection of two or more wires to make a pigtail connection. These closed end connectors feature translucent nylon insulation and a tin-plated copper sleeve that is rated to be used in up to 300V and is RoHS compliant. Translucent nylon insulation. Tin-plated copper sleeve. Meets UL 94V-2 Flammability Classification. Rated for continuous operating temperature of 105°C (221°F).

[Read More](#)

SKU: 901225

Price: \$13.66

Categories: [Closed End](#)

Product Description
