



12-10 Gauge Flanged Spade Terminal, 10 Stud, Bag Of 100

Vinyl-insulated, flanged spade terminals are connectors that are used to connect a single wire, while allowing for a connection to a screw or stud type electrical connection. The vinyl material acts as an economic insulation type, while the flanged shape of the spade terminal fastens onto the stud nut. This prevents the terminal from pull-out and creates a more secure connection. Because of this, insulated flanged spade terminals are commonly used in high vibration electrical applications. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

SKU: 403105

Price: \$27.34

Categories: [Spade](#)

Product Description



12-10 Gauge Flanged Spade Terminal, 6 Stud, Bag Of 100

Vinyl-insulated, flanged spade terminals are connectors that are used to connect a single wire, while allowing for a connection to a screw or stud type electrical connection. The vinyl material acts as an economic insulation type, while the flanged shape of the spade terminal fastens onto the stud nut. This prevents the terminal from pull-out and creates a more secure connection. Because of this, insulated flanged spade terminals are commonly used in high vibration electrical applications. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)**SKU:** 403065**Price:** \$27.29**Categories:** [Spade](#)

Product Description



12-10 Gauge Flanged Spade Terminal, 8 Stud, Bag Of 100

Vinyl-insulated, flanged spade terminals are connectors that are used to connect a single wire, while allowing for a connection to a screw or stud type electrical connection. The vinyl material acts as an economic insulation type, while the flanged shape of the spade terminal fastens onto the stud nut. This prevents the terminal from pull-out and creates a more secure connection. Because of this, insulated flanged spade terminals are commonly used in high vibration electrical applications. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)**SKU:** 403085**Price:** \$26.53**Categories:** [Spade](#)

Product Description

12-10 Gauge High Temp Butt Connector, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 323005

Price: \$39.86

Categories: [Butt](#)

Product Description



12-10 Gauge High Temp Terminal, 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

SKU: 36310

Price: \$22.76**Categories:** [Spade](#)

Product Description



12-10 Gauge Piggy Back, .250 Female Push-On Terminal, Bag Of 100

Push-on, piggy back terminals are female type connectors that mate with male push-on terminals, and have an additional male blade to connect a primary and secondary wire, all in one connection. Push-on, piggy back terminals are popular in auto and marine applications, but are also used in various other electrical applications. Most economical insulated terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)**SKU:** 400685**Price:** \$23.78**Categories:** [Piggy Back](#)

Product Description



12-10 Gauge Spade Terminal, 10 Stud, Bag Of 100

Most economical insulated terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

SKU: 463105

Price: \$21.73

Categories: [Spade](#)

Product Description



12.3 Oetiker Style Stepless Clamp, 100 A Bag

9.8-12.3 mm or 25/64-31/64 Fits BT-4 And BT-41 Tubing

[Read More](#)

SKU: 12.3-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



12.3 Oetiker Style Stepless Clamp, 25 A Bag

9.8-12.3 mm or 25/64-31/64 Fits BT-4 And BT-41 Tubing

[Read More](#)

SKU: 12.3-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



12.8 Oetiker Style Stepless Clamp, 100 A Bag

10.3-12.8 mm or 13/32-1/2

[Read More](#)

SKU: 12.8-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



12.8 Oetiker Style Stepless Clamp, 25 A Bag

10.3-12.8 mm or 13/32-1/2

[Read More](#)

SKU: 12.8-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



12/3 Cord Assy. 20A/125V, Replacement For Bunn #23799.0001

Fits Models AXIOM, Axiom, CDBC, CDBC APS, CDBC Series, CDBC-DV, CDBC, CDBC APS, CDBC-LPTC, CDBC, CDBC, CEZ, CEZF, CWTF-35, H5E, H5M, H5X, H5X-18-120, H5X-40-208, HC-1, HC-2, HC-3, HIGH VOLUME GRINDER, LCA-2 PC, LCR-2, LCR-2 PC, LCR-2A, LCR-2A PC, SINGLE, SINGLE SH 1.5, SINGLE SH 1.75, SINGLE SH DBC, SINGLE TF DBC

[Read More](#)

SKU: 23799.0001

Price: \$22.09

Categories: [Bunn](#)

Product Description

12/3 Cord Assy. 20A/125V
