



## 12-10 Gauge Closed End Connector Terminal, Bag of 100

Closed End connectors are ideal for making a simple connection of two or more wires to make a pigtail connection. These closed end connectors feature translucent nylon insulation and a tin-plated copper sleeve that is rated to be used in up to 300V and is RoHS compliant. Translucent nylon insulation. Tin-plated copper sleeve. Meets UL 94V-2 Flammability Classification. Rated for continuous operating temperature of 105°C (221°F).

[Read More](#)

**SKU:** 901225

**Price:** \$13.66

**Categories:** [Closed End](#)

### Product Description

---



## 12-10 Gauge Terminal, 100

Vinyl-insulated, flared spade connectors that are ideal for making a simple connection while allowing for a secure electrical connection. The economic insulation on the spade terminal prevents the terminal from pulling out, providing a secure connection. The spade terminals are ideal for electrical applications such as building wire; 1000

[Read More](#)

**SKU:** 403105**Price:** \$27.34**Categories:** [Spade](#)

## Product Description

---



## 12-10 Gauge Flanged Spade Terminal, 6 Stud, Bag Of 100

Vinyl-insulated, flanged spade terminals are connectors that are used to connect a single wire, while allowing for a connection to a screw or stud type electrical connection. The vinyl material acts as an economic insulation type, while the flanged shape of the spade terminal fastens onto the stud nut. This prevents the terminal from pull-out and creates a more secure connection. Because of this, insulated flanged spade terminals are commonly used in high vibration electrical applications. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)**SKU:** 403065**Price:** \$27.29**Categories:** [Spade](#)

## Product Description

---



## 12-10 Gauge Flanged Spade Terminal, 8 Stud, Bag Of 100

Vinyl-insulated, flanged spade terminals are connectors that are used to connect a single wire, while allowing for a connection to a screw or stud type electrical connection. The vinyl material acts as an economic insulation type, while the flanged shape of the spade terminal fastens onto the stud nut. This prevents the terminal from pull-out and creates a more secure connection. Because of this, insulated flanged spade terminals are commonly used in high vibration electrical applications. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

**SKU:** 403085

**Price:** \$26.53

**Categories:** [Spade](#)

### Product Description

---



## 12-10 Gauge High Temperature Butt Connector,

High temperature butt connectors are used to mate, connect, or terminate wires in high temperature butt connections. They are used in high temperature applications where standard connectors are not ideal for use in high temperature environments such as motors, ovens or other applications where the connector can melt. Constructed from high temperature materials, they have a continuous operating temperature of 250° C and an intermittent rating of 300° C.

[Read More](#)

**SKU:** 323005**Price:** \$39.86**Categories:** [Butt](#)

## Product Description

---



## 12-10 Gauge High Temp Spade Terminal, 10 Stud, Bag Of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)**SKU:** 363105**Price:** \$22.76**Categories:** [Spade](#)

## Product Description

---



## 12-10 Gauge Piggy Back, .250 Female Push-On Terminal, Bag Of 100

Push-on, piggy back terminals are female type connectors that mate with male push-on terminals, and have an additional male blade to connect a primary and secondary wire, all in one connection. Push-on, piggy back terminals are popular in auto and marine applications, but are also used in various other electrical applications. Most economical insulated terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

**SKU:** 400685

**Price:** \$23.78

**Categories:** [Piggy Back](#)

### Product Description

---



## 12-10 Gauge Stud, Bag Of 100

Most economical insulated terminal available. PVC insulation sleeve is securely fastened to butted seam barrel. Insulation has flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated to 600 volts maximum, building wire; 1000 volts maximum, 105° C.

[Read More](#)

**SKU:** 46310

**Price:** \$21.78

Categories: [Spade](#)

## Product Description

---



### 12.3 Oetiker Style Stepless Clamp, 100 A Bag

9.8-12.3 mm or 25/64-31/64 Fits BT-4 And BT-41 Tubing

[Read More](#)

**SKU:** 12.3-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

## Product Description

---



### 12.3 Oetiker Style Stepless Clamp, 25 A Bag

9.8-12.3 mm or 25/64-31/64 Fits BT-4 And BT-41 Tubing

[Read More](#)

**SKU:** 12.3-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

## Product Description

---



## 12.8 Oetiker Style Stepless Clamp, 100 A Bag

10.3-12.8 mm or 13/32-1/2

[Read More](#)

**SKU:** 12.8-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

### Product Description

---



## 12.8 Oetiker Style Stepless Clamp, 25 A Bag

10.3-12.8 mm or 13/32-1/2

[Read More](#)

**SKU:** 12.8-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

### Product Description

---