



12.3 Oetiker Style Stepless Clamp, 25 A Bag

9.8-12.3 mm or 25/64-31/64 Fits BT-4 And BT-41 Tubing

[Read More](#)

SKU: 12.3-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



12.8 Oetiker Style Stepless Clamp, 100 A Bag

10.3-12.8 mm or 13/32-1/2

[Read More](#)

SKU: 12.8-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



12.8 Oetiker Style Stepless Clamp, 25 A Bag

10.3-12.8 mm or 13/32-1/2

[Read More](#)

SKU: 12.8-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



12/3 Cord Assy. 20A/125V, Replacement For Bunn #23799.0001

Fits Models AXIOM, Axiom, CDBC, CDBC APS, CDBC Series, CDBCD-DV, CDBCf, CDBCf APS, CDBCf-LPTC, CDBCfP, CDBCP, CEZ, CEZF, CWTF-35, H5E, H5M, H5X, H5X-18-120, H5X-40-208, HC-1, HC-2, HC-3, HIGH VOLUME GRINDER, LCA-2 PC, LCR-2, LCR-2 PC, LCR-2A, LCR-2A PC, SINGLE, SINGLE SH 1.5, SINGLE SH 1.75, SINGLE SH DBC, SINGLE TF DBC

[Read More](#)

SKU: 23799.0001

Price: \$19.99

Categories: [Bunn](#)

Product Description

12/3 Cord Assy. 20A/125V



12/3 SJ00W Black Round Cord 250 Foot Spool

12/3 300-Volt Portable Cord is ideal for wiring portable tools, small motors and equipment. This cord features 3 copper conductors with wax- and tissue-paper insulation and a rubber jacket. This product is highly flexible with good tensile strength, elongation and aging. Class-K copper conductors, 250 ft. cable offers heat-, moisture- and oil-resistant, flexible rubber jacket, 12-gauge black stranded construction Wax- and tissue paper filler wrapped around the conductors to promote easier removal of the jacket, RoHS compliant, UL listed and CSA certified for indoor and outdoor use

[Read More](#)

SKU: 12-3

Price: \$522.21

Categories: [Cord](#)

Product Description



12/4 SJ00W 250 Foot Sp

12/4 300-Volt Portable Cord is ideal for wiring portable tools, small motors and equipment. This cord features 4 copper conductors with wax- and tissue-paper insulation and a rubber jacket. This product is highly flexible with good tensile strength, elongation and aging. Class-K copper conductors, 250 ft. cable offers heat-, moisture- and oil-resistant, flexible rubber jacket, 12-gauge black stranded construction Wax- and tissue paper filler wrapped around the conductors to promote easier removal of the jacket, RoHS compliant, UL listed and CSA certified for indoor and outdoor use

[Read More](#)

SKU: 12-4
Price: \$589.42
Categories: [Cord](#)

Product Description



13.3 Oetiker Style Stepless Clamp, 100 A Bag

10.8-13.3 mm or 27/64-17/32

[Read More](#)

SKU: 13.3-100
Price: \$19.20
Categories: [Oetiker Style Bag Of 100](#)

Product Description



13.3 Oetiker Style Stepless Clamp, 25 A Bag

10.8-13.3 mm or 27/64-17/32

[Read More](#)

SKU: 13.3-25
Price: \$6.75
Categories: [Oetiker Style Bag Of 25](#)

Product Description



13.8 Oetiker Style Stepless Clamp, 100 A Bag

11.3-13.8 mm or 7/16-35/64

[Read More](#)

SKU: 13.8-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



13.8 Oetiker Style Stepless Clamp, 25 A Bag

11.3-13.8 mm or 7/16-35/64

[Read More](#)

SKU: 13.8-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



14 Gauge Black RVI Wire, 100 Foot Roll

Non Stock, Item Must Be Ordered. 14 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29141-05

Price: \$43.58

Categories: [14 Gauge](#)

Product Description



14 Gauge Blue RVI Wire, 100 Foot Roll

Non Stock, Item Must Be Ordered. 14 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29141-03

Price: \$43.58

Categories: [14 Gauge](#)

Product Description
