



15.3 Oetiker Style Stepless Clamp, 25 A Bag

12.8-15.3 mm or 1/2-39/64

[Read More](#)

SKU: 15.3-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



15.7 Oetiker Style Stepless Clamp, 100 A Bag

13.2-15.7 mm or 33/64-5/8 Fits BT-63 And BT-61
Tubing

[Read More](#)

SKU: 15.7-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



15.7 Oetiker Style Stepless Clamp, 25 A Bag

13.2-15.7 mm or 33/64-5/8 Fits BT-63 And BT-61 Tubing

[Read More](#)

SKU: 15.7-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



15000 Grain Rechargeable Water Softener, Fpt 3/4 9 Inches Wide x 21 Inches Tall

To Reduce Down, Use Bushings 110A-EB For 1/4 Fpt Or 110A-EC For 3/8 Fpt.

[Read More](#)

SKU: WS15000

Price: \$144.68

Categories: [Softeners](#)

Product Description



16 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-05

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Blue Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-03

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-07

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-04

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-01

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-02

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Yellow Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-06

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16-14 Gauge High Temp

High temperature butt connector, mate, connect, or terminate high temperature butt connector. High temperature applications where temperatures can exceed 250°C. Ideal for use in high temperature motors, ovens or other applications where temperatures can melt. Constructed for continuous operating temperatures and intermittent rating.

[Read More](#)

SKU: 352105
Price: \$23.37
Categories: [Ring](#)

Product Description
