16 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

Read More

SKU:	29161-05
Price:	$32.55
Categories:	16 Gauge

Product Description

---

16 Gauge B
Foot Roll

Non Stock, Item Mu
up wire is ideal for
automotive and ma
insulation is moistu
protection against
105°C, rated for 60
exceed the specific
J1128. CSA file no.
Specifications print
where exposure to

221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

Read More

SKU: 29161-03

Price: $32.55

Categories: 16 Gauge

Product Description

---

16 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

Read More

SKU: 29161-07

Price: $32.55

Categories: 16 Gauge

Product Description

---

16 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

Read More

SKU:	29161-04
Price:	$32.55
Categories:	16 Gauge

Product Description

---

16 Gauge R
Roll

Non Stock, Item Mu
up wire is ideal for
automotive and ma
insulation is moistu
protection against
105°C, rated for 60
exceed the specific
J1128. CSA file no.
Specifications print
where exposure to
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

Read More

SKU: 29161-01

Price: $32.55

Categories: 16 Gauge

Product Description

---

16 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

Read More

SKU: 29161-02

Price: $32.55

Categories: 16 Gauge

Product Description

---

16 Gauge Yellow Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

Read More

SKU:	29161-06
Price:	$32.55
Categories:	16 Gauge

Product Description

16-14 Gaug
High Temp

High temperature b
mate, connect, or t
temperature butt c
temperature applic
applications where
ideal for use in high
motors, ovens or ot
can melt. Construct
continuous operatin
intermittent rating
Read More

SKU: 352105

Price: $23.37

Categories: Ring

Product Description

16-14 Gauge #10 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

Read More

SKU: 452105

Price: $16.80

Categories: Ring

Product Description

16-14 Gauge #4 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

Read More

SKU: 452045

Price: $15.23

Categories: Ring

Product Description

16-14 Gauge #6 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

Read More

SKU: 352065

Price: $23.06

Categories: Ring

Product Description

16-14 Gauge #6 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

Read More

SKU: 452065

Price: $20.09

Categories: Ring

Product Description