



15.3 Oetiker Style Stepless Clamp, 25 A Bag

12.8-15.3 mm or 1/2-39/64

[Read More](#)

SKU: 15.3-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



15.7 Oetiker Style Stepless Clamp, 100 A Bag

13.2-15.7 mm or 33/64-5/8 Fits BT-63 And BT-61 Tubing

[Read More](#)

SKU: 15.7-100

Price: \$19.20

Categories: [Oetiker Style Bag Of 100](#)

Product Description



15.7 Oetiker Style Stepless Clamp, 25 A Bag

13.2-15.7 mm or 33/64-5/8 Fits BT-63 And BT-61 Tubing

[Read More](#)

SKU: 15.7-25

Price: \$6.75

Categories: [Oetiker Style Bag Of 25](#)

Product Description



15000 Grain Rechargeable Water Softener, Fpt 3/4 9 Inches Wide x 21 Inches Tall

To Reduce Down, Use Bushings 110A-EB For 1/4 Fpt Or 110A-EC For 3/8 Fpt.

[Read More](#)

SKU: WS15000

Price: \$135.85

Categories: [Softeners](#)

Product Description



16 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-05

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge B Foot Roll

Non Stock, Item Mu
up wire is ideal for
automotive and ma
insulation is moistu
protection against r
105°C, rated for 60
exceed the specific
J1128. CSA file no. 2
Specifications print
where exposure to
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-03

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-07

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-04

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge R Roll

Non Stock, Item Mu
up wire is ideal for
automotive and ma
insulation is moistu
protection against r
105°C, rated for 60
exceed the specific
J1128. CSA file no. 2
Specifications print
where exposure to
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-01

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-02

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16 Gauge Yellow Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

SKU: 29161-06

Price: \$32.55

Categories: [16 Gauge](#)

Product Description



16-14 Gauge High Temp

High temperature butt connector terminal is used to mate, connect, or terminate high temperature butt connectors in high temperature applications where the wire can melt. Constructed for continuous operating and intermittent rating.

[Read More](#)

SKU: 352105

Price: \$23.37

Categories: [Ring](#)

Product Description
