

# 14 Gauge Black RVI Wire, 100 Foot Roll

Non Stock, Item Must Be Ordered. 14 gauge RVI hookup wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### **Read More**

**SKU:** 29141-05

**Price:** \$43.58

Categories: 14 Gauge

### **Product Description**



# 14 Gauge B Foot Roll

Non Stock, Item Mu up wire is ideal for a automotive and ma insulation is moistu protection against r 105°C, rated for 60 exceed the specific J1128. CSA file no. 2 Specifications print where exposure to 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### Read More

**SKU:** 29141-03

**Price:** \$43.58

Categories: 14 Gauge

#### **Product Description**



# 14 Gauge Brown RVI Wire, 100 Foot Roll

14 gauge RVI hook-up wire is ideal for machine tools,

control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at

temperatures not exceeding 140°F. CSA type TEW FT1.

#### Read More

**SKU:** 29141-07

**Price:** \$43.58

Categories: 14 Gauge

### **Product Description**



# 14 Gauge Green RVI Wire, 100 Foot Roll

Non Stock, Item Must Be Ordered. 14 gauge RVI hookup wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### **Read More**

**SKU:** 29141-04

**Price:** \$43.58

Categories: 14 Gauge

### **Product Description**



### 14 Gauge R Foot Roll

Non Stock, Item Mu up wire is ideal for automotive and ma insulation is moistu protection against in 105°C, rated for 60 exceed the specific J1128. CSA file no. Specifications print where exposure to 221°F or where exp exceeding 140°F. CSA type TEW FT1.

Read More

**SKU:** 29141-01

**Price:** \$43.58

**Categories:** 14 Gauge

#### **Product Description**



# 14 Gauge White RVI Wire, 100 Foot Roll

Non Stock, Item Must Be Ordered. 14 gauge RVI hookup wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### Read More

**SKU:** 29141-02

**Price:** \$43.58

Categories: 14 Gauge

### **Product Description**



# 14 Gauge Yellow RVI Wire, 100 Foot Roll

Non Stock, Item Must Be Ordered. 14 gauge RVI hookup wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

#### **Read More**

**SKU:** 29141-06

**Price:** \$43.58

Categories: 14 Gauge

### **Product Description**