



Asse 1022 Backflow Preventer, 3/8 Flare x 3/8 Flare x 1/4 Barb

ASSE 1022 vented dual check back flow preventer protects the connected plumbing and drinking water from the corrosive effects of CO2 gas. The CO2 gas mixed with water in a carbonator tank downstream from the back flow preventer exerts back pressure on the discharge primary check valve on every pumping cycle. If this check valve becomes fouled and leaks, the CO2 gas and water mixture will exhaust through the vent fitting. The secondary check insures that it cannot pass to the inlet or contact any brass or copper from the connected plumbing. The simple internal construction is easy to clean. It utilizes a lead free brass body and stainless steel discharge retainer. Under no circumstance is the CO2 gas and water mixture exposed to the lead-free brass inlet or the connected plumbing.

[Read More](#)

SKU: 19-0897F

Price: \$50.49

Categories: [Backflow](#)

Product Description



ASSE 1022 Backflow Preventer, 3/8 Flare x 3/8 Mpt x 1/4 Barb

ASSE 1022 vented dual check back flow preventer protects the connected plumbing and drinking water from the corrosive effects of CO2 gas. The CO2 gas mixed with water in a carbonator tank downstream from the back flow preventer exerts back pressure on the discharge primary check valve on every pumping cycle. If this check valve becomes fouled and leaks, the CO2 gas and water mixture will exhaust through the vent fitting. The secondary check insures that it cannot pass to the inlet or contact any brass or copper from the connected plumbing. The simple internal construction is easy to clean. It utilizes a lead free brass body and stainless steel discharge retainer. Under no circumstance is the CO2 gas and water mixture exposed to the lead-free brass inlet or the connected plumbing.

[Read More](#)

SKU: 19-0897

Price: \$50.49

Categories: [Backflow](#)

Product Description



Inline Check Valve Tube x Tube 3/8 x 3/8

John Guest Mfg, Sold Each Or 10 A Bag. Produced at the request of leading companies in the Drinks Dispense Industry, the Super Speedfit Acetal Single Check Valve ensures protection against reversal of flow. The low headloss design and fast installation time make the valve the ideal selection. The valve is designed for use with liquids, it is not suitable for air and vacuum applications. Working Pressures and Temperatures 10 Bar at 20°C, 7 Bar at 65°C intermittent hot water, Minimum temperature 1°C, Typical 'crack open' pressure 0.02 Bar

[Read More](#)

SKU: 38SCV

Price: \$11.73

Categories: [Backflow](#)

Product Description



Pvc Check Valve Barb x Barb 1/4

Max pressure 125 Psi, Max Temp 140°F, Cracking Pressure 1 Psi.

[Read More](#)

SKU: PVCBCK-4

Price: \$10.92

Categories: [Backflow](#)

Product Description



Pvc Check Valve Barb x Barb 3/8

Max pressure 125 Psi, Max Temp 140°F, Cracking Pressure 1 Psi.

[Read More](#)

SKU: PVCBCK-6

Price: \$11.81

Categories: [Backflow](#)

Product Description



Stainless Steel Double Check Valve Barb x Barb 3/8

[Read More](#)

SKU: 9041

Price: \$12.32

Categories: [Backflow](#)

Product Description

Stainless Steel Double Check Valve Flare x Flare 3/8



[Read More](#)

SKU: S470D-66

Price: \$12.32

Categories: [Backflow](#)

Product Description

Stainless Steel Single Check Valve Flare x Female Flare 3/8



ASSE Rated 1032, NSF 18 listed, 200 psi Temperature 33°F to 90°F

[Read More](#)

SKU: S470-6F6

Price: \$12.68

Categories: [Backflow](#)

Product Description

Stainless Steel Single Check Valve Flare x Mpt 3/8 x 1/4



ASSE Rated 1032, NSF 18 listed, 200 psi Temperature 33°F to 90°F

[Read More](#)

SKU: S470-6P4

Price: \$12.67

Categories: [Backflow](#)

Product Description

Watts Asse 1022 Backflow Preventer, Max. Pressure 150psi Or 10 bar, Max. Temperature 130°F Or 54°C 61657



Item Non Stock, Must Be Ordered. Certified to ANSI/NSF Standard 18, Manual Food and Beverage Dispensing Equipment ASSE 1022 Approved Dual Check with Atmospheric Vent. 316 stainless steel body for corrosion resistance. All rubber compounds comply with FDA food additive regulations. Streamlined body design minimizes pressure loss and cavitation. Atmospheric port provides visual indication of failure of the second check.

[Read More](#)

SKU: SD3-LS

Price: \$240.54

Categories: [Backflow](#)

Product Description
