

## 16-14 Gauge .250 Female Push On Fully Insulated Terminal, Bag of 100



The Nylon insulation sleeve is molded onto the barrel. Transparent nylon allows for easy inspection of connection and is resistant to deformation. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 894005

**Price:** \$15.67

**Categories:** [Push On](#)

### Product Description

---



## 16-14 Gauge Push On, Insulated Terminal, Bag of 100

This series is the most popular series available. The PVC insulation is fastened to the barrel with a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 492005

**Price:** \$15.95

**Categories:** [Push On](#)

## Product Description

---



## 16-14 Gauge .250 Male Push On Fully Insulated Terminal, Bag of 100

The Nylon insulation sleeve is molded onto the barrel. Transparent nylon allows for easy inspection of connection and is resistant to deformation. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Temperature rating: 105° C (221° F).

[Read More](#)

**SKU:** 834005

**Price:** \$15.48

**Categories:** [Push On](#)

## Product Description

---



## 16-14 Gauge 1/4 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 352145

**Price:** \$24.97

**Categories:** [Ring](#)

### Product Description

---



## 16-14 Gauge 1/4 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

**SKU:** 452145

**Price:** \$14.92

**Categories:** [Ring](#)

## Product Description

---



### 16-14 Gauge 3/8 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 352385

**Price:** \$24.21

**Categories:** [Ring](#)

## Product Description

---



### 16-14 Gauge Vinyl Insulated Stud Ring, High Temp Terminal, Bag of 100

This series is the most available. The PVC is fastened to the butt with a flared entry for easy maximum, building and fixtures. Industrial wire range. Temperature

[Read More](#)

**SKU:** 452385DL**Price:** \$19.98**Categories:** [Ring](#)

## Product Description

---



## 16-14 Gauge 5/16 Stud Ring, High Temp Terminal, Bag of 100

High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)**SKU:** 352565**Price:** \$24.01**Categories:** [Ring](#)

## Product Description

---



## 16-14 Gauge 5/16 Stud Ring, Vinyl Insulated Terminal, Bag of 100

This series is the most economical insulated terminal available. The PVC insulation sleeve is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures. Industry standard color-coding indicates wire range. Temperature rating: 105° C (22

[Read More](#)

**SKU:** 452565

**Price:** \$14.92

**Categories:** [Ring](#)

### Product Description

---



## 16-14 Gauge Terminal, B

Vinyl-insulated butted terminals that are used on a single wire. The vinyl insulation and the barrel type of terminal barrel are great for marine applications that utilize wire to terminate. This series is the most economical insulated terminal available. The PVC insulation is securely fastened to the butted seam barrel. The insulation has a flared entry for easier wire insertion. Industry standard color-coding indicates wire range. Rated 600 volts maximum, building wire; 1000 volts maximum, signs and fixtures.

F).

[Read More](#)

**SKU:** 422005

**Price:** \$15.76

**Categories:** [Butt](#)

## Product Description

---



## 16-14 Gauge Closed End Connector Terminal, Bag of 100

Closed End connectors are ideal for making a simple connection of two or more wires to make a pigtail connection. These closed end connectors feature translucent nylon insulation and a tin-plated copper sleeve that is rated to be used in up to 300V and is RoHS compliant. Translucent nylon insulation. Tin-plated copper sleeve. Meets UL 94V-2 Flammability Classification. Rated for continuous operating temperature of 105°C (221°F).

[Read More](#)

**SKU:** 901215

**Price:** \$9.92

**Categories:** [Closed End](#)

## Product Description

---

## 16-14 Gauge High Temp Butt Connector, Bag Of 100



High temperature butt connectors are terminals that mate, connect, or terminate a single wire. High temperature butt connectors are ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. This series is ideal for use in high temperature applications like motors, ovens or other applications where terminals can melt. Constructed of steel plated nickel. Rated for continuous operating temperature of 482° C (900° F), intermittent rating of 649° C (1200° F).

[Read More](#)

**SKU:** 322005

**Price:** \$36.42

**Categories:** [Butt](#)

### Product Description

---