



## 15.3 Oetiker Style Stepless Clamp, 25 A Bag

12.8-15.3 mm or 1/2-39/64

[Read More](#)

**SKU:** 15.3-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

### Product Description

---



## 15.7 Oetiker Style Stepless Clamp, 100 A Bag

13.2-15.7 mm or 33/64-5/8 Fits BT-63 And BT-61 Tubing

[Read More](#)

**SKU:** 15.7-100

**Price:** \$19.20

**Categories:** [Oetiker Style Bag Of 100](#)

### Product Description

---



## 15.7 Oetiker Style Stepless Clamp, 25 A Bag

13.2-15.7 mm or 33/64-5/8 Fits BT-63 And BT-61 Tubing

[Read More](#)

**SKU:** 15.7-25

**Price:** \$6.75

**Categories:** [Oetiker Style Bag Of 25](#)

### Product Description

---



## 15000 Grain Rechargeable Water Softener, Fpt 3/4 9 Inches Wide x 21 Inches Tall

To Reduce Down, Use Bushings 110A-EB For 1/4 Fpt Or 110A-EC For 3/8 Fpt.

[Read More](#)

**SKU:** WS15000

**Price:** \$144.68

**Categories:** [Softeners](#)

### Product Description

---



## 16 Gauge Black Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFPA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-05

**Price:** \$32.55

**Categories:** [16 Gauge](#)

### Product Description

---



## 16 Gauge B Foot Roll

Non Stock, Item Mu  
up wire is ideal for  
automotive and ma  
insulation is moistu  
protection against r  
105°C, rated for 60  
exceed the specific  
J1128. CSA file no. 2  
Specifications print  
where exposure to  
221°F or where exp

exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-03

**Price:** \$32.55

**Categories:** [16 Gauge](#)

## Product Description

---



## 16 Gauge Brown Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-07

**Price:** \$32.55

**Categories:** [16 Gauge](#)

## Product Description

---



## 16 Gauge Green Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-04

**Price:** \$32.55

**Categories:** [16 Gauge](#)

### Product Description

---



## 16 Gauge Red Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.



exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-01

**Price:** \$32.55

**Categories:** [16 Gauge](#)

## Product Description

---



## 16 Gauge White Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293.

Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-02

**Price:** \$32.55

**Categories:** [16 Gauge](#)

## Product Description

---



## 16 Gauge Yellow Rvi Wire 100 Foot Roll

Non Stock, Item Must Be Ordered. 16 gauge RVI hook-up wire is ideal for machine tools, control cabinets, automotive and marine applications. The thermoplastic insulation is moisture resistant and provides extra protection against nicks and cuts. UL style 1015/1230, 105°C, rated for 600 volts. Manufactured to meet or exceed the specifications of the RVI, NFDA, ANSI and J1128. CSA file no. 22035, UL file no. E51293. Specifications printed on wire. Use in internal wiring where exposure to temperatures does not exceed 221°F or where exposure to oil at temperatures not exceeding 140°F. CSA type TEW FT1.

[Read More](#)

**SKU:** 29161-06

**Price:** \$32.55

**Categories:** [16 Gauge](#)

### Product Description

---



## 16-14 Gauge High Temp

High temperature butt connector is used to mate, connect, or terminate high temperature butt connectors in high temperature applications where the wire can melt. Constructed for continuous operating and intermittent rating.

[Read More](#)

**SKU:** 352105

**Price:** \$23.37

**Categories:** [Ring](#)

## Product Description

---